



VEN TOAN Co., Ltd

VENTO CO., LTD

17-19 Street D12, Tay Thanh Ward, Tan Phu Dist, HCM City

Tel : +848 62679227-62679228 Fax : +848 62679229

Email : vento@vento.com.vn; website : www.vento.com.vn

IMPREGNATING AGENT SK-45

INTRODUCTION

Masonry water repellent “Impregnating Agent SK-54” is a water dilutable Potassium Methyl Siliconate used for imparting a colourless water repellent surface finish to mineral building material without significantly reducing water vapour permeability.



AVANTAGE

- Good penetration depth.
- The pores and capillaries are not sealed and hence water vapour permeability is not reduced.
- There are no change in appearance of the substrate; the treated surface does not become glossy.
-

APPLICATION

Brick, Masonry, Concret, Stone, etc.

SPECIFICATION

Product code	Impregnating Agent SK-45
Appearance	Straw color clear liquid
Viscosity	12 cSt
Specific Gravity (25oC)	1,25 – 1,30
Solid contain (w/w)	42 - 45

DILUTION

SK-54 should be diluted with ordinary tap water before use. The quality of diluted SK-54 usually required for different substrate are :

Substrate	Coverage	Dilution
Unpainted plastered surface	Two liberal appl.0.5 – 0,8 L/m ²	1:10 - 1:25
Hot brick, tile soaking on continuous machine	2 - 3 L/m ²	1:50 - 1:100
Cool brick, tile soaking by hand	0.5-1 L/m ²	1:10 - 1:15
Concret	0.1-0.5 L/m ²	1:10 - 1:12

PRODUCT ORIGIN : KOREA